PCM-3110C PCM-3112


1-slot PCMCIA Module

2-slot PCMCIA Module



Features

- Supports Type I, II, III PCMCIA cards
- 16-bit data bus
- Busy status LED



Features

- 2 PCMCIA slots
- Bootable from linear Flash card or ATA Flash, ATA HDD
- 16-bit data bus
- Busy status LED

Specifications

General

Standard Complies with PCMCIA V2.10 and JEIDA 4.1 **PC Card Format** Accepts Type I/II/III PCMCIA cards

Data Bus 16-bit

Supports (PC/104 or external drive) Secondary - PCMCIA Card drive with PC/104 bus

Drive 1 main PCMCIA slot extended to 2nd slot

with extended (TEAC) FDD extended to 3.5" FDD bay

BIOS Programmable 32 KB SMD boot Flash BIOS

Mechanical and Environmental

Dimension (L x W) 96 mm x 90 mm (3.8" x 3.5") Weight 0.092 kg (0.203 lb)

 Operating Temperature Operating: 0 ~ 60° C (32 ~ 140° F)

Storage: -40 ~ 85° C (-40 ~ 18° F)

 Operating Humidity 0% ~ 90% relative humidity, non-condensing

Power

■ Power Supply Voltage +5 V, ±5 % tolerance on power supply

 Power Consumption +5 V @ 70 mA (typical)

Packing List

- 1 x PCM-3110C SBC
- 1 x Manual

Ordering Information

Standard

- PCM-3110C-0000 PCMCIA Module

Specifications

General

Standard Complies with PCMCIA V2.10 and JEIDA 4.1 spec

 PC Card Format Accepts Type I/II/III PCMCIA cards

Data Bus 16-bit

Secondary Features 2 PCMCIA drives

BIOS Programmable 32 KB SMD-type boot EEPROM BIOS

Mechanical and Environmental

- Dimension (L x W) 96 mm x 90 mm (3.8" x 3.5")

Weight 0.1 kg (0.22 lb)

• Operating Temperature Operating: $0 \sim 60^{\circ}$ C ($32 \sim 140^{\circ}$ F)

Storage: -40 ~ 85° C (-40 ~ 185° F)

 Operating Humidity 0% ~ 90% relative humidity, non-condensing

■ Power Supply Voltage +5 V, ±5 % tolerance on power supply

 Power Consumption +5 V @ 70 mA (typical)

Packing List

■ 1 x PCM-3112 SBC

1 x Manual

Ordering Information

Standard

PCM-3112-0000

2-slot PCMCIA module