


# PCM-3115

# PCM-3116

2-slot Card Bus Module

2-slot mini PCI Module



PCM-3115



## Features

- High-performance (PC/104-Plus)
- Low power consumption (Hardware Suspend)
- Complies with PC Card 95/97/98, Card-32 (32 Bit), PCMCIA V2.1/JEIDA 4.2 (16 Bit)
- Accepts Type I/II/III PCMCIA cards
- Supports 2 PCMCIA slots (when Type III card used in Slot 2, Slot 1 will be occupied too)

## Specifications

### General

- **Chipset** Ricoh Card Bus Controller
- **16-bit Legacy Mode** YES (3E0/3E2 I/O port) support
- **GPIO Support** YES
- **PCI way Legacy DMA** YES supported
- **Data Bus** 32-Bit data bus (Compliant with PCI Bus Specification 2.1)
- **PCI Interface** 3.3 V interface (5 V tolerant)
- **H/W Configuration** Plug & Play automatic detection & configuration
- **S/W Driver** Supports Windows® NT 4.0, Windows® 95/98/2000

### Mechanical and Environmental

- **Dimension (L x W)** 96 mm x 90 mm (3.8" x 3.5")
- **Weight** 0.094 kg (0.207 lb)
- **Operating Temperature** Operating: 0 ~ 60° C (32 ~ 140° F)  
Storage: -40 ~ 85° C (-40 ~ 185° F)
- **Operating Humidity** 0% ~ 90% relative humidity, non-condensing

### Power

- **Power Supply Voltage** +5 V, ± 5 % tolerance on power supply
- **Power Consumption** +5 V @ 70 mA (typical)


## Packing List

- 1 x Startup manual
- 1 x CD-ROM (Manual, Driver, Utility)
- 1 x PCM-3115

## Ordering Information

### Standard

- **PCM-3115-00B1** 2-slot Card Bus module



PCM-3116



## Features

- Supports 2 miniPCI devices
- High performance (PC/104-Plus)
- Compliant with PCI v2.1

## Specifications

### General

- **Data Bus** 32-Bit data bus (Compliant with PCI Bus Specification 2.1)
- **PCI Interface** 3.3 V interface (5 V tolerant)

### Mechanical and Environmental

- **Dimension (L x W)** 96 mm x 90 mm (3.8" x 3.5")
- **Weight** 0.094 kg (0.207 lb)
- **Operating Temperature** Operating: 0 ~ 60° C (32 ~ 140° F)  
Storage: -40 ~ 85° C (-40 ~ 185° F)
- **Operating Humidity** 0% ~ 90% relative humidity, non-condensing

### Power

- **Power Supply Voltage** +5 V, ± 5 % tolerance on power supply

## Packing List

- 1 x Startup manual
- 1 x PCM-3116

## Ordering Information

### Standard

- **PCM-3116-00A1** 2-slot miniPCI module